

## Sailboat Winterizing Checklist

	item	Notes
1 E	ngine + Generator	
	Fill fuel tank and add stabilizer	П
	Change oil and filter	
	Change fuel filter and water separator	
	Check/replace coolant	
	Run antifreeze through raw water cooling system	
	Check raw water strainer - should be full of antifreeze     Check impeller, remove if you want	
	Close seacock on water, leave open on land	
	Place engine key at seacock as reminder for Spring	
	0	
	0	
2 [	washington Cristoms	
	reshwater Systems	
	<ul> <li>Pump out holding tank(s)</li> <li>Add and pump antifreeze through heads (to tank and out)</li> </ul>	U n
	<ul> <li>Run antifreeze through bilge pump</li> <li>Drain sinks and all other freshwater passages (live well, deck washdown pump, freshwater tanks) of any</li> </ul>	
	.wator.	
	Run antifreeze through sinks and all other freshwater passages (live well, deck washdown pump, etc)	
	Drain shower sump	
	0	
	0	
3 B	elow Decks	
	Set up trickle charger for battery (or remove battery)	
	Remove cushions or store sideways	
	Close propane valves remove portable canisters	
	Verify bilge pump works	
	Secure all ports and hatches (double check seals)	
	Turn off circuit breakers except for bilge and smoke alarms	
	o Remove food	
	Add moisture absorber or dehumidifier	
	0	
	0	
<b>4</b> A	bove Decks/Hull	
	Pressure wash hull and deck	П
	Remove, clean, store sail in a dry space	
	Inspect standing rigging for corrossion, cracks, and wear	
	Inspect running rigging for wear (attach a feeder line and pull the haylards through the mast)	
	Check chainplates for proper seals	
	Check that all turnbuckles have rings or pins	
	Inspect keel for cracks (typically toward the front of the keel)	
	Inspect hatches, windows, and deck fittings for proper seals	<u> </u>
	0	<u> </u>
	0	
(TOTAI	_S	0/40 )